

EAVE SEALANT DETAIL 1'-0" MAX. BUTYL SEALANT MUST COME IN CONTACT WITH THE DRIP EDGE TO FORM A WEATHERTIGHT SEAL 12 WALL PANEL 2" THICKNESS -LOW FLOATING CLIP [HW-230] SUPERLOK PANEL NON-SKINNING BUTYL SEALANT [HW-549] BETWEEN PANEL RIBS FIELD NOTCH PANEL 12-11 x 1 PANCAKE HEAD 1 1/2" LEGS AND BEND PAN TO FORM OPEN HEM SELF—TAPPER [FASTENER #13A] @ 12" O.C. GUTTER STRAP [FL-310] © EVERY OTHER RIB 1/8 x 3/16 POP RIVET -[FASTENER #14] 1 1/2" (2) PER STRAP -MOISTURE BARRIER (NOT BY MBCI) BOX GUTTER W/DRIP EDGE [T-5271] 5/8" PLYWOOD MIN. 1/2" 1/2" -CONT. 3/8" PLYWOOD SPACER (NOT BY MBCI) (NOT BY MBCI) 1/4-14 x 1 LONG-LIFE — 'TYPE AB' SELF-TAPPER W/WASHER [FASTENER #2B] - 14-10 x 1 'TYPE A' SELF-TAPPER W/WASHER [FASTENER #18] (2) PER CLIP 1 1/2" -WOOD BLOCKING (NOT BY MBCI) BOX GUTTER W/DRIP EDGE [T-5271] NOTE: WALL PANEL-NOTE: REFERENCE TYPICAL TRIM LAP SECTIONS DO NOT USE THIS DETAIL ON ROOF SLOPES LESS THAN 3:12

O/O DIMENSION (SEE PLAN)