

Houston, TX 877/713-6224
 Adel, GA 888/446-6224
 Atlanta, GA 877/512-6224
 Atwater, CA 800/829-9324
 Dallas, TX 800/653-6224

Indianapolis, IN 800/735-6224
 Lubbock, TX 800/758-6224
 Memphis, TN 800/206-6224
 Oklahoma City, OK 800/597-6224
 Omaha, NE 800/458-6224

Phoenix, AZ 888/533-6224
 Richmond, VA 800/729-6224
 Rome, NY 800/559-6224
 Salt Lake City, UT 800/874-2404
 San Antonio, TX 800/598-6224



Commercial/Industrial

PRODUCT INFORMATION

RUSTIC C WALL PANEL ALLOWABLE UNIFORM LOADS IN POUNDS PER SQUARE FOOT

22 Gauge RUSTIC thickness (0.0256"), Fy = 33 ksi, Fu = 45 ksi								
SPAN TYPE	LOAD TYPE	SUPPORT SPACING						
		3 Ft.	4 Ft.	5 Ft.	6 Ft.	7 Ft.	8 Ft.	9 Ft.
1-span	NEGATIVE WIND LOAD	103.53	58.24	37.27	25.88	19.02	14.56	11.50
	LIVE LOAD/DEFLECTION	103.53	58.24	37.27	25.88	19.02	14.56	11.50
2-span	NEGATIVE WIND LOAD	101.72	57.66	37.03	25.77	18.95	14.52	11.48
	LIVE LOAD/DEFLECTION	101.72	57.66	37.03	25.77	18.95	14.52	11.48
3-span	NEGATIVE WIND LOAD	126.19	71.76	46.16	32.15	23.66	18.13	14.34
	LIVE LOAD/DEFLECTION	126.19	71.76	46.16	32.15	23.66	18.13	14.34
4-span	NEGATIVE WIND LOAD	118.09	67.08	43.13	30.02	22.09	16.93	13.39
	LIVE LOAD/DEFLECTION	118.09	67.08	43.13	30.02	22.09	16.93	13.39

Notes:

- Strength calculations based on the 2012 AISI Standard "North American Specification for the Design of Cold-formed Steel Structural Members."
- Allowable loads are applicable for uniform loading and spans without overhangs.
- LIVE LOAD/DEFLECTION load capacities are for those loads that push the panel against its supports. The applicable limit states are flexure, shear, combined shear and flexure, web crippling at end and interior supports, and a deflection limit of L/60 under strength-level loads.
- NEGATIVE WIND LOAD capacities are for those loads that pull the panel away from its supports. The applicable limit states are flexure, shear, combined shear and flexure, and a deflection limit of L/60 under 10-year wind loading.
- Panel pullover and Screw pullout capacity must be checked separately using the screws employed for each particular application when utilizing this load chart.
- Effective yield strength has been determined in accordance with section A2.3.2 of the 2012 NAS specification.
- The use of any accessories other than those provided by the manufacturer may damage panels, void all warranties and will void all engineering data.
- This material is subject to change without notice. Please contact MBCI for most current data.

The Engineering data contained herein is for the expressed use of customers and design professionals. Along with this data, it is recommended that the design professional have a copy of the most current version of the *North American Specification for the Design of Cold-Formed Steel Structural Members* published by the American Iron and Steel Institute to facilitate design. This Specification contains the design criteria for cold-formed steel components. Along with the Specification, the designer should reference the most current building code applicable to the project jobsite in order to determine environmental loads. If further information or guidance regarding cold-formed design practices is desired, please contact the manufacturer.