



CONCEALED FASTENING SYSTEMS

SLIMLINE®

The Slimline® roof panel system offers a sleek contemporary profile ideal for residential and light commercial applications. This system offers a concealed fastener attachment. Slimline® panels must be specified as striated or striated with minor ribs. Slimline® cannot be endlapped.



Features and Benefits:

- UL 580 ratings are available, as well as UL 790, Class A for external fire, roof assembly for UL 263 for internal fire and the UL 2218 Class 4 impact rating.
- Slimline® carries Florida approval.

Product Specifications

- Applications: Roof
- Coverage Widths: 16"
- Rib Height: 1"
- Minimum Slope: 3:12
- Panel Attachment: Concealed Fastening System
- Gauges: 29 (standard); 26 (optional)
- Finishes: Striations (standard); Minor Rib Striations (optional)
- Coatings: Galvalume Plus®, Signature® 200

www.mbc.com | shop.mbc.com

HOUSTON | 281.407.6915
ADEL, GA | 888.514.6062
ATLANTA | 678.337.1619
ATWATER, CA | 209.445.3891

ENNIS, TX | 469.256.8255
INDIANAPOLIS | 317.364.4329
LUBBOCK, TX | 806.224.2724

MEMPHIS, TN | 662.298.2337
OKLAHOMA CITY | 405.492.6968
PHOENIX | 480.630.3022

ROME, NY | 315.371.4330
SALT LAKE CITY | 385.715.2952
SAN ANTONIO | 210.888.9768



CONCEALED FASTENING SYSTEM

SLIMLINE®

CATEGORY	CHARACTERISTIC	TEST METHOD	PURPOSE	RESULT
ENVIRONMENTAL	Impact Resistance	UL 2218	Determines Impact Resistance of prepared Roof Covering Materials	Class 4 Rating
	Room Fire Performance	UL 790	Standard for Standard Test Methods for Fire Tests of Roof Coverings	See Class A Fire Rating Data Sheet
FIRE RESISTANCE	Room Fire Performance	UL 263	Standard for Fire Tests of Building Construction and Materials	For use in Design Nos. P225, P227, P230, P237, P265, P268, P508, P510, P512, P701, P711, P720, P722, P726, P731, P734, P801, P815, P819.
	Uplift Resistance	ASTM E 1592	Provides a standard procedure to evaluate or confirm structural performance under uniform static air pressure difference	See Load Chart Section
STRUCTURAL	Gravity Loads	AISI S100	North American Specification for the Design of Cold-Formed Steel Structural Members	See Section Properties and Allowable Load Table Section
	Roof Performance - Underwriters Laboratories	UL 580	Determines the uplift resistance of roof assemblies consisting of the roof and roof coverings materials	Class 90 Rating - Construction Number 529
ROOF LISTINGS	Roof Performance - Florida Approval	UL 580 UL 1897 UL 790	Florida product approval is the approval of products and systems, which comprise the building envelope and structural frame, for compliance with the structural requirements of the Florida Building Code.	See FL# 11903.4
	Roof Performance - Texas Department of Insurance	UL 580 UL1897	TWIA provides windstorm and hail insurance in areas exposed to hurricanes and currently provides windstorm and hail coverage in the following 14 "first tier" Texas coastal counties: Aransas, Brazoria, Calhoun, Cameron, Chambers, Galveston, Jefferson, Kenedy, Kleberg, Matagorda, Nueces, Refugio, San Patricio and Willacy.	See RC-357



Descriptions and specifications contained herein were in effect at the time this publication was approved for printing. In a continuing effort to refine and improve products, MBCI reserves the right to discontinue products at any time or change specifications and/or designs without incurring obligation. To ensure you have the latest information available, please inquire or visit our website at www.mbc.com. Application details are for illustration purposes only and may not be appropriate for all environmental conditions, building designs or panel profiles. Projects should be designed to conform to applicable building codes, regulations and accepted industry practices. If there is a conflict between this manual and project erection drawings, the erection drawings will take precedence. MBCI's insulated metal panel product line is manufactured by Metl-Span®.